

Industrial Nozzle



Style #366-BC

- Corrosion resistant cast brass construction. Ideal for marine, offshore, industrial or other corrosive environments
- Constant flow selectable gallonage nozzle with multi flow settings
- Select flow remains constant regardless of pattern change
- Multi pattern detents for positive positioning of pattern
- Combination of fog and straight stream
- Flush without shutting down
- Standard optimum operating pressure 100 PSI(7 bar)
- Conforms to all aspects of NFPA 1964 (Spray nozzles, shutoff and tips) 2003 edition

PROTEK
NFPA1964
COMPLIANT




STYLE	INLET	LENGTH	WEIGHT LBS	FLOW	
				GPM	LPM
366-BC	1-1/2"	8.5"	8.8	30-60-95-125	115-230-360-475

www.protektfire.com

sales@protektfire.com

UNIQUE FEATURES ON PROTEK INDUSTRIAL NOZZLES



- 1 316 stainless steel spinning teeth ensure corrosion resistance and durability
- 2 Laser etched anodized indicating bands for long life and easy use (No stick labels to fade and come loose)
- 3 Large metal flow select ring (Easy to change flow setting even with a wet glove)
- 4 Major component made from brass (UNS C83600, ASTM B62/B584) for a long in serving life
- 5 Choice of inlet thread or connection
- 6 Stainless steel inlet screen catches solid before they enter nozzle (only things that gets through can be flushed without shutting down)
- 7 New improved handle with two reinforced metal pieces on each side to ensure breakage free
- 8 Heavy duty chrome plated metal balls ensures a smooth action and long dependable service life
- 9 Each nozzle etched with a unique series number. Aids identification, tracks manufacturing date and warranty
- 10 Flow pattern detents gives positive positioning