

# Constant Gallonage Nozzle



## Style #372

- Tough durable design, simple and easy to operate
- Simplified the nozzle training and maintenance
- Quality stream and excellent reach at variety of pressure:
- Excellent performance at pressure as little as 50 PSI (3.5 bar)
- Multi pattern detents for positive positioning of pattern
- The nozzles are easily customized to meet your specific requirement
- Low through life maintenance due to the use of top quality material and design
- Conforms to all aspects of NFPA 1964, 2003 edition



## Specification

Style	Inlet	Length	Weight (Lbs)	Flow	
				GPM	LPM
372	1-1/2" or 2-1/2"	8"	3.8	95@75psi 125@75psi 60@100psi 95@100psi 125@100psi	360@3.5 bar 475@5.2 bar 230@7 bar 360@7 bar 475@7 bar



- ① 316 stainless steel spinning teeth ensure corrosion resistance and durability. Molded teeth also available
- ② Can be field retrofitted to optional flows and pressure
- ③ 100 psi, 75 psi or 50 psi models
- ④ New improved handle with two reinforced metal pieces on each side to ensure the breakage free
- ⑤ Stainless steel inlet screen catches solid before they enter nozzle
- ⑥ Heavy duty chrome plated shutoff balls ensures a smooth action and long dependable service life
- ⑦ Each nozzle etched with a unique series numbers. Aids identification, Tracks manufacturing date and warranty
- ⑧ Flow pattern detents gives positive positioning

#372 Nozzle Pressure & Flow Options

Nozzle Pressure (psi)	95@75	125@75	60@100	95@100	125@100
50	78	102	42	67	88
75	95	125	52	82	108
100	110	144	60	95	125