

Constant Gallonage Nozzle



Style #373 Midrange

- Tough durable design, simple and easy to operate
- Simplified the nozzle training and maintenance
- Quality stream and excellent reach at variety of pressures
- Excellent performance at pressure as little as 50 PSI (3.5 bar)
- Multi pattern detents for positive positioning of pattern
- The nozzles are easily customized to meet your specific requirement
- Low through life maintenance due to the use of top quality material and design
- Conforms to all aspects of NFPA 1964, 2003 edition



Specification

Style	Inlet	Length	Weight (Lbs)	Flow	
				GPM	LPM
373	1-1/2"	10"	5.8	150 @50 psi	550@3.5 bar
				150@75 psi	550@5.2 bar
				175@75 psi	660@5.2 bar
				200@75 psi	750@7 bar
				150@100 psi	550@7 bar
				175@100psi	660@7bar
				200@100psi	750@7bar
				225@100psi	850@7bar



- ① 316 stainless steel spinning teeth ensure corrosion resistance and durability. Molded teeth also available
- ② Can be field retrofitted to optional flows and pressure
- ③ 100 psi, 75 psi or 50 psi models
- ④ New improved handle with two reinforced meal pieces on each size to ensure the breakage free
- ⑤ Stainless steel inlet screen catches solid before they enter nozzle
- ⑥ Heavy duty chrome plated shutoff balls ensures a smooth action and long dependable service life
- ⑦ Each nozzle etched with a unique series numbers. Aids identification, Tracks manufacturing date and warranty
- ⑧ Flow pattern détentes gives positive positioning

#373 Nozzle Pressure & Flow Options

Nozzle Pressure (psi)	150 @ 50	150 @ 75	175 @ 75	200 @ 75	150 @ 100	175 @ 100	200 @ 100	225 @ 100
50	150	122	143	163	106	124	141	159
75	184	150	175	200	130	152	173	195
100	212	173	202	231	150	175	200	225