




Self-Educting Master Stream Nozzle



1-1/2" Industrial Grade Hose
with Quick Change Fitting, 9 feet long

Quick Change Fitting
Complete with Cap



Style #888-BC

- Rugged bronze construction
- The fixed gallonage nozzle rated 100 PSI is available with choice of 350, 500, or 750 GPM
- A master stream nozzle with "built-in" eductor
- Proportions and delivers either water or foam to the target
- Designed for use with Class A and B foam, including AFFF and fluoroprotein
- Installation of Protek self-educating foam nozzle turns existing monitor into a foam station
- Proportioning capability of 0.5, 1, 3, and 6%
- Percentage us easily set with an interchangeable orifice plates provided
- Adjustable from straight stream to fog
- Comes with 9 feet long industrial grade pick up hose with quick and secure attachment to the nozzle
- Drum pick up kit available
- Weight: 22 Lbs

WWW.PROTEKFIREFIRE.COM



Self-Educting Master Stream Nozzle

WWW.PROTEKFIREFIRE.COM

Style	Flow (GPM)	Throw (Straight Stream) @100PSI	Throw (Narrow Fog) @100PSI	Water Inlet	Foam Inlet	Proportioning Rate
888-BC	350	140 ft	100 ft	2-1/2"	1-1/2"	0.5,1,3, 6%
	500	175 ft	100 ft			
	750	190 ft	100 ft			

