

EN Selectable Gallonage Nozzle



EN SELECTABLE GALLONAGE NOZZLES

- EN 15182-2 Type 3 and DIN 14367 Compliant (Constant selectable gallonage nozzle with multiple flow settings)
- One click to Flashover pattern position. Raised lug on the bumper for the Flashover fog pattern
- Maximum flow position indicator
- Exceptional lightweight and compact
- Stainless steel spinning teeth ensure corrosion resistance and durability
- New improved handle with two reinforced metal pieces to ensure breakage free
- Heavy duty chrome plated metal shutoff ball ensures a smooth action and long dependable service life
- Superb wide fog pattern for optimum personal protection or optional fixed teeth for dense fog
- Ergonomic shape and designed pistol grip for comfort



#2360 & #2361



#2365 & #2366



#2368

EN Selectable Gallonage Nozzle



Raised lug for flashover fog pattern



Newly improved handle with two reinforced metal pieces on each side to prevent breakage

#2368-TP

Products data sheet

STYLE	FLOWRATES	INLET	WEIGHT	LOW EXPANSION FOAM TUBE	MEDIUM EXPANSION FOAM TUBE
#2360	20-40-100-150 L/min @6 bar	1" BSP F	1.2 kg	#210	#225
#2361	50-100-150-230 L/min @6 bar	1" BSP F	1.2kg	#210	#225
#2365	70-130-230-400 L/min @6 bar	1.5" BSP F BS 336 Inst.	1.6 kg	#213	#226
#2366	100-250-350-500 L/min @6 bar	1.5" BSP F BS 336 Inst.	1.6 kg	#213	#226
#2368	285-500-600-800-950 L/min @6 bar	2.5" BSP F BS 336 Inst.	2.5kg	#215	#227
#2368-TP	285-500-600-800-950 L/min @6 bar	2.5" BSP F BS 336 Inst.	4.2 kg	#215	#227