



Style #922
Remote Controlled Monitor



Features

- Durable Lightweight Aluminum Construction
- Horizontal Rotation 180 Degree or 330 Degree
- Vertical Travel 150 Degree
- Full 2" Vaned Waterway To Improve Stream Performance
- Advanced Nozzles with 3 Flow Settings
 - 818-45 15, 30, 45 GPM
 - 818-125 60, 95, 125 GPM
 - 818-350 200, 250, 350 GPM
- The Spring-Loaded Baffle Allows For Quick And Easy Change of Flows Selection With A Simple Turn of Baffle Head
- Gear Motors Totally Enclosed And Sealed
- Enclosed Stainless Steel Gears
- Manual Override
- 12 VDC or 24 VDC System
- Control Box With 4 Function Switches
- Optional Control Box with Joystick

Style	Flow	Thread		Dimensions			Weight
		Outlet	Inlet	Width	Depth	Height	
922/W 818-45	15, 30 or 45 GPM	1.5"	2" NPT	8.5"	8"	11"	16 lbs
922/W 818-125	60, 95 or 125 GPM	1.5"	2" NPT	8.5"	8"	11"	16 lbs
922/W 818-350	200, 250 or 350 GPM	1.5"	2" NPT	8.5"	8"	11"	16 lbs